

Greip SPK Module

OBO-A1-0010-18 Product Specification

Approved By	Checked By	Prepared By

Revision History

Version	Date	Description	Author
X1	2025-7-16	Performance tuning	HSJ

Doc No.		File Name	OBO-A1-0010-18 Product Specification				
Establish Dep.	Engineering	Establish Date	2025/7/16	Rev.	X1	Sheet No.	1/11

Table Of Contents

- 1.** Scope
- 2.** Environmental Requirements
- 3.** Electrical Requirements
- 4.** Acoustical Requirements
- 5.** Drive circuit
- 6.** Polarity Requirement
- 7.** Test Climatic Condition
- 8.** Test Method
- 9.** General Requirements
- 10.** General Reliability
- 11.** Mechanical Layout and Dimensions
- 12.** Weight
- 13.** Package

Doc No.		File Name	OBO-A1-0010-18 Product Specification				
Establish Dep.	Engineering	Establish Date	2025/7/16	Rev.	X1	Sheet No.	2/11

1.Scope

This specification contains electrical, mechanical, acoustical, and environmental requirements for this model

2.Environmental Requirements

Every material used in the speaker is in accordance with the RoHS.。

3.Electrical Requirements

3.1 Greip Module

Rater Power :	1mW	(0.179Vrms)
Max Power	3mW	(0.31 Vrms)
Short Term Max Power :	5mW	(0.4 Vrms)

3.2 LSR SPK

Impedance :	16 $\Omega \pm 15\%$ ohm at 1KHz
Rater Power :	1mW (0.179Vrms)
Short Term Max Power :	8mW (0.51 Vrms)

3.3 MEMS SPK

Maximum positive voltage :	20 V
Upper operating frequency limit :	80K Hz

4.Acoustical Requirements

4.1 Sound Pressure Level: 103 $\pm$ 2dB @1mW (0.179Vrms) 1KHz.

4.2 Rated Frequency Range : 20–40KHz
Frequency Response See Figure 1, Table


4.3 THD: @20 Hz -1.5K Hz <1% 2.5KHz-10KHz <2.5% 1mW (0.179Vrms). See Figure 2, Table

4.4 Rub & Buzz :

The input power shall be set at 3 mW (0.31Vrms). Using an audio oscillator Sweep from 50 to 2K Hz in the free air. There shall be no buzzes, rattles, nor spurious noises.

Doc No.		File Name	OBO-A1-0010-18 Product Specification				
Establish Dep.	Engineering	Establish Date	2025/7/16	Rev.	X1	Sheet No.	3/11


Rated Frequency Response Curve
@Level=0.179 Vrms (1mW)



Limit

频率	20	50	500	1000	2000	3000	5000	6500	8000	10000	11000
上限	+3	+2	+2	+2	+2	+3	+3	+4.5	+5	+5	+5
下限	-3	-2	-2	-2	-2	-3	-3	-4.5	-5	-5	-5

Total Harmonic Distortion Curve
@Level=0.179Vrms(1mW)



Limit

	20	1500	2500	10000
Limit	1	1	2.5	2.5

Doc No.		File Name	OBO-A1-0010-18 Product Specification				
Establish Dep.	Engineering	Establish Date	2025/7/16	Rev.	X1	Sheet No.	4/11

5. Drive circuit

In Figure 3 the driving circuit is shown.




Figure 3

NO.	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT	Remarks
1	Supply Voltage	In normal function	3.0	3.7	5.5	V	
2	Supply Current 1	En = low at 3.7V			2	uA	
3	Supply Current 2	En = High, Mute = low at 3.7V, Input lever = 0V	0.8		1	mA	
4	Supply Current 3	En = High, Mute = low at 3.7V Input lever = 0.179V Pink noise	0.9		1.5	mA	
5	Input lever				0.7	V	

Doc No.		File Name	OBO-A1-0010-18 Product Specification				
Establish Dep.	Engineering	Establish Date	2025/7/16	Rev.	X1	Sheet No.	5/11

6.PolarityRequirement

When a DC source “+” polarity is attached to speaker’s “+” polarity, and “-” polarity is attached to speaker’s “-”polarity, the diaphragm will move forward

7.Test Climatic Condition

Ambient temperature: 21°C- 25°C,preferably at 23°C
Humidity 25%- 75%, atmosphere, 86kPa ~ 106kPa, Refer to IEC 268-1

8.Test Method

8.1 SPL and Frequency Response Curve, with IEC 60318-4.

The drive power is 1 mW , and swept sine-wave rang is 20Hz to 20K Hz ,with a R40 of test sequence

8.2 THD

Tested per Section 7.1 and driven at rated power , sweep at specified
Frequency rang with R40 test sequence

Test setup



Test jig



GRAS RA0045-S1
IEC 60318-4 Ear
Simulator



GRAS 42AG
Multifunction Sound
Calibrator

Doc No.		File Name	OBO-A1-0010-18 Product Specification				
Establish Dep.	Engineering	Establish Date	2025/7/16	Rev.	X1	Sheet No.	7/11

9. General Requirements

9.1 Operating Temperature Range : -20°C to +60°C

9.2 Storage Temperature Range : -25°C to +65°C

10. General Reliability

Immediately after reliability test, the samples shall be stored under climatic Conditions such as normally exist in ordinary rooms or laboratories. Unless otherwise noted, the recovery period shall be 4 hours at least before Performance testing.

10.1 Load Test: Input power 3mW(0.31 Vrms), Pink Noise signal, Duration 96 hours, Duration of recovery 2hours at 25°C (room temperature).


10.2 Max Power Test: Input power 5mW (0.4Vrms), Pink Noise signal1 min ON,2 min OFF for 10 cycle times, Duration of recovery 2hoursat 25°C(room temperature).

10.3 Humidity Test: Temperature +40°C, Relative Humidity 90% ~ 95% Duration 96 hours, Duration of recovery - 2hours at 25°C (room temperature).

10.4 Heat Resistance Test: +65°C Duration 96 hours, Duration of recovery - 2hours at 25°C (room temperature).

10.5 Cold Resistance Test: -25°C Duration 96 hours, Duration of recovery - 2 hours at 25°C (room temperature).

10.6 Temperature Shock Test: (-25°C/+65°C) 10cycles. 0.5 hour at each temperature, Transition time <5 min, Duration of recovery 2 hours.




10.7 Drop Test: Drop form height 0.8m to the ground (concrete surface) in 3 angles. Each angle for 3 cycle times.

Doc No.		File Name	OBO-A1-0010-18 Product Specification				
Establish Dep.	Engineering	Establish Date	2025/7/16	Rev.	X1	Sheet No.	8/11

11. Mechanical Layout and Dimensions

Unit: mm



10	PCBA	1	FR4 With Travos PA
9	Frame	1	PC+GF
8	Ring	1	Aluminum alloy
7	Edge	1	Silicon dioxide
6	Voice Coil	1	CCAW
5	Cover	1	Aluminum alloy
4	Washer	1	SPCC + Nickel plating
3	Magnet	1	NdFeB + Nickel plating
2	T-iron	1	SPCC + Nickel plating
1	Mesh	1	Nylon
NO	LSR PART NAME	Q'TY	MATERIAL

Doc No.		File Name	OBO-A1-0010-18 Product Specification				
Establish Dep.	Engineering	Establish Date	2025/7/16	Rev.	X1	Sheet No.	9/11

12. Weight

±0.05 g

13. Package

	MATERIAL	P/N	REMARKS
1	Product	92-80-0035	2800 pcs
2	TRAY	55-80-5006	20 pcs
3	PE Bag	56-00-5001	2pcs/Carton
4	Carton	55-00-5000	Carton/20 Tray/2800pcs

+正极 -负极
① 焊盤面朝上擺放

② 140 PCS products/盤

③ PE袋

如左圖所示，包裝成兩捆
每捆1400pcs=140pcs*10
共10盤，用PE袋包裝好，纏繞膠布如圖所示

2 Bundles=20 盤

RoHS標籤

入庫標籤

合格標籤

④ Carton

以透明膠帶封箱，封箱時為“工”字形封箱

				UNITS: mm	GENERAL TOLERANCE	DRAW:	PART NO.: P-080-A1-0010-01
				DATE: 2020/04/28	X. ± 0.20 X" ± 3.0"	CHECKED:	TITLE: Greip 10mm SPKAR
				SCALE: 1:1	.X ± 0.15 .X" ± 2.0"	APPROVE:	DRAWING NO.: P-080-A1-0010-01
X1		ZCL	2024/9/20	SIZE: A4	.XX ± 0.10 .XX" ± 1.0"		
REV.	ECN NO.	DRAW	DATE	SHEET: 1/1	.XXX ± 0.05 .XXX" ± 0.5"	3rd ANGLE PROJECTION	OBO Pro.2

Doc No.		File Name	OBO-A1-0010-18 Product Specification				
Establish Dep.	Engineering	Establish Date	2025/7/16	Rev.	X1	Sheet No.	10/11

